

CEILING & FLOOR CEILING SUSPENDED



Features

- Gold Fin™ Anti Corrosion • Natural Wind by CHAOS Swing
- Wireless Remote Control • Sleep Mode Auto Operation
- Auto Operation • Auto Restart • Soft Dry Operation Mode
- Auto-Touch Air Filter (Anti - Bacterial) • 24hr On/Off Timer

Models

HV - C186BLA0 / HV - C246BLA0



Indoor Unit			HV - C186BLA0	HV - C246BLA0
Cooling Capacity		kW	5.30	7.00
		Btu/h	18,000	24,000
Heating Capacity		kW	-	-
		Btu/h	-	-
Power Input	Cooling	kW	1.85	2.60
	Heating	kW	-	-
EER	Cooling	Btu/h/W	9.73	9.23
COP	Heating	W/W	-	-
Current	Cooling / Heating	A	0.35	0.35
Fan	Fan Type		Cross Flow Fan	Cross Flow Fan
	Motor Output (W) x Number of unit		79*1	79*1
	Air Flow rate (H/M/L)	CMM	15/13/11	18/16/14
		CFM	530/460/390	636/566/495
Coil	Row x Stages x FPI	mm	2R x 14C x 20	2R x 14C x 20
Dimension	Indoor (WxHxD)	mm	1200 * 615 * 205	1200 * 615 * 205
		inch	47.2 * 24.2 * 8.07	47.24 * 24.21 * 8.07
Weight	Indoor	kg(lbs)	30 (66.1)	30 (66.1)
Sound Level (H/M/L)		db(A)±3	43/40/37	50/48/46
Piping	Liquid	mm(inch)	6.35 (1/4)	6.35 (1/4)
Connections	Gas	mm(inch)	15.88 (5/8)	15.88 (5/8)
Drain	ID	mm	17/14	17/14
Dehumidification rate		l/h	1.73	2.11
Outdoor Unit				
Power Supply		/ V / Hz	1/220-240/50	1/220-240/50
Power Supply Cable (outdoor)		No*mm ³	3*2.5 (Including Earth)	3*2.5 (Including Earth)
Power and Transmission Cable		No*mm ³	4*0.75 (Including Earth)	4*0.75 (Including Earth)
Dimensions		mm	870 * 655 * 320	870 * 655 * 320
		inch	34.2 * 25.8 * 12.6	34.2 * 25.8 * 12.6
Net Weight		kg(lbs)	57 (126)	62 (136)
Compressor			Rotary	Rotary
			1*QP325PCB	1*QP407PAB
		cc	Induction 700	Induction 700
Refrigerant			SUNISO 4GSI or ATMOS M60	SUNISO 4GSI or NM56
		g(oz)	1000 (35.5)	1750 (61.73)
			R22	R22
Heat Exchanger			Capillary Tube	Capillary Tube
			(2R * 30C * 21FPI) x 1	(2R * 28C * 18FPI) x 1
Fan	Side / Top		Side	Side
		CMM(CFM)	47 (1660)x1	47 (1660)x1
Noise Level (H/L)		db(A)±3	52	52
Max. Piping length		m	30	30
Max. Elevation		m	15	15
Stuffing Quantity		20 / 40ft	46 / 96	46 / 96

Note: Due to our policy of innovation some specifications may change without notification.

Specifications