



Features

- Gold Fin™ Anti Corrosion • Soft Dry Operation Mode
- One-Touch Air Filter (Anti-Bacterial) • Auto Swing
- 7 Hour OFF Setting Timer Mode • Wireless Remote Controller
- Neuro Fuzzy Control (optional) • Child Lock Function
- Auto Restart • Jet Cool Operation

Models

TP - C488TL(A)C*1



Specifications

Indoor Unit			TP - C488TL(A)C*1
Cooling Capacity		kW	14.07
		Btu/h	48,000
Heating Capacity		kW	-
		Btu/h	-
Power Input	Cooling	kW	5.0
	Heating	kW	-
EER	Cooling	Btu/h/W	9.60
COP	Heating	W/W	-
Current	Cooling / Heating	A	8.5
Fan	Air Flow rate (H/M/L)	CMM	31
		CFM	1094
Dimension	Indoor (WxHxD)	mm(inch)	590 * 1850 * 440
			(23.7 * 72.8 * 17.3)
Weight	Indoor	kg(lbs)	60 (132)
Sound Level (H/M/L)		db(A)±3	56 / 54 / 52
Piping	Liquid	mm(inch)	9.52 (3/8)
Connections	Gas	mm(inch)	19.05 (3/4)
Drain	OD / ID	mm	16.5 / 12.5
Dehumidification rate		l/h	6
Indoor Unit			
Running Current	Cooling	A	8.5
	Heating	A	-
Power Supply		∅ / V / Hz	3,380-415,50
Power Supply Cable (outdoor)		No*mm ³	5*3.3
Power and Transmission Cable		No*mm ³	4*0.82
Dimensions	W*H*D	mm(inch)	900*1160*370
Net Weight		kg(lbs)	(35.43*45.67*14.57)
Compressor	Type		95 (209)
	Qty x Model		Scroll
	Motor Type		1*JT160BCBY1L
	Oil Charge Volume	cc	PSC
	Oil Type		1 500-1 700
Refrigerant	Charge (at 7.5m)	g(oz)	DAHPNE SE56P
	Type		4 200 (148)
	Control		R22
Heat Exchanger	Rows x Column x FPI		Capillary
Fan	Discharge Direction	Side / Top	Side
	Air Flow Rate	CMM(CFM)	105 (3708)
Noise Level (H/L)	Sound Press, 1m	db(A)±3	62
Max. Piping length	Main Piping	m	30
Max. Elevation	Indoor Unit - Outdoor Unit	m	15
Stuffing Quantity	Without S/Parts	20 / 40ft	13 / 29

Note: Due to our policy of innovation some specifications may change without notification.