



S0964C
S1264C
S1864C
S2464C

- Powerful Cooling
- Multi-stage Tropical Compressor
- 4-way Swing
- Jet Cool
- Ez-washable
- Gold Fin
- 14 FPI

- Refroidissement puissant
- Compresseur tropical multi-stade
 - Swing à 4-voies
- Jet refroidissement
- Ez-lavable
- Gold Fin
- 14 FPI



Specifications Spécifications Techniques

Model			Cooling Only S0964C	Cooling Only S1264C	Cooling Only S1864C	Cooling Only S2464C
Cooling Capacity		kW	2.52	3.37	5.04	6.74
		Btu/hr	8,600	11,500	17,200	23,000
Heating Capacity		kW	-	-	-	-
		Btu/hr	-	-	-	-
Input	Cooling	W	920	1,290	1,900	2,800
	Heating	W	-	-	-	-
Running Current	Cooling	A	4.2	6.0	9.2	13.0
	Heating	A	-	-	-	-
Power Supply		øV, Hz	1, 220-240, 50	1, 220-240, 50	1, 220-240, 50	1, 220-240, 50
E.E.R	Cooling	W/W	2.74	2.61	2.65	2.41
		Btu/hrW	9.35	8.91	9.05	8.21
C.O.P	Heating	W/W	-	-	-	-
ENERGY Efficiency Class	Cooling/Heating		-	-	-	-
Noise Level (SoundPress,1m)	Indoor(H/M/L)	dB(A)±3	34/30/27	39/33/28	41/38/34	44/40/35
	Outdoor, Max	dB(A)±3	48	49	54	54
Air Flow	Indoor, Max	m ³ /min	6.5	8	15	19
	Outdoor, Max	m ³ /min	20	20	42	42
Dehumidification Rate		l/h	1	1.3	1.8	2.8
Refrigerant & Charge (at 7.5 m)		g(oz)	-	-	R22, 1,000(35.3)	R22, 1,500(52.9)
SVC Valve	Liquid	mm(inch)	6.35(1/4)	6.35(1/4)	6.35(1/4)	9.52(3/8)
	Gas	mm(inch)	9.52(3/8)	12.7(1/2)	12.7(1/2)	15.88(5/8)
Dimensions (W*H*D)	Indoor	mm	890*290*210	890*290*210	1,030*325*250	1,030*325*250
	Outdoor	mm	717*498*229	717*498*229	840*577*276	840*577*276
Net Weight	Indoor	kg(lbs)	10(22)	10(22)	17.0(37.5)	17.0(37.5)
	Outdoor	kg(lbs)	30.3(66.8)	34(75.0)	46.0(101.4)	48.0(105.8)

Note: Specifications, design and feature are subject to change without prior notice.

Note: les caractéristiques, design et fonctionnalité sont susceptibles d'être changés sans préavis.